

TESTRONIX™ Coating Thickness Gauges

Coating Thickness Gauge Ferrous



Model TCT - F01

It is best way to check dry film thickness of non magnetic organic coating on Ferrous substrates. Non-destructively measure thickness of non-conductive coating (Paint, enamel, rubber plastic etc.) on magnetic metal (iron) substrates.

- Based on Eddy current measurement method
- Supplied in an industrial Carrying Case
- Flexible lead Measuring Probes set of 5 Calibration Foils and Zero Disks.
- Option for single and Multiple point calibration.
- Thickness Range : 0-1250 Microns
- Accuracy : ± 2.5 Microns

Coating Thickness Gauge non Ferrous



Model TCT - NF01

Non-Ferrous models non-destructively measure thickness of non-conductive coating (Paint, enamel, rubber plastic etc.) on non-magnetic metal (Aluminum, copper, zinc, Tin, etc.) substrates .

- Supplied in an industrial Carrying Case
- Flexible lead Measuring Probes set of 5 Calibration Foils and Zero Disks.
- Option for single and Multiple point calibration.
- Based on Eddy current measurement method
- Thickness Range : 0-1250 Microns
- Accuracy : ± 2.5 Microns

Coating Thickness Gauge Ferrous & non Ferrous



Model TCT - FNF01

It is true professional product for material thickness measurement or coating thickness measurements and flaw detection.

- Non-destructively measure thickness of non-conductive coating (Paint, enamel, rubber plastic etc.) on magnetic (iron) & non-magnetic metal (Aluminum, copper, zinc, Tin, etc.) substrates .
- Auto-Hold reading on the display
- Based on Eddy current measurement method
- Flexible lead Measuring Probes set of 5 Calibration Foils and Zero Disks.
- Thickness Range : 0-1250 Microns
- Accuracy : ± 2.5 Microns

OUR OTHER PRODUCTS :-

					
Ultra Low Temperature Deep Freezer	Humidity Chamber	Cupping Machine	Paint Impact Resistance Tester	Scratch Hardness Tester Motorised	Scratch Hardness Tester Hand Operated

Our Valued Customers



All above logos are the sole property of their respective owners and are used purely for depiction purposes only

Head Office : Presto Stantest Private Limited

I-42, DLF Industrial Area Phase-I, Delhi Mathura Road, Faridabad 121003, Haryana, India
 P : +91 129 4272727 E : info@prestogroup.com

Branches :

Mumbai

503-504 B, Fair link Centre, Opp. Fame Adlab, Behind Mongini's Off Link Road Andheri (West), Mumbai 400058
 P : +91 022 42957052, 42957053
 E : west@prestogroup.com

Kolkata

93, 3rd Floor, Karnani Estate 209, A.J.C. Bose Road Kolkata-700017. West Bengal
 P : +91 033 40612012
 E : east@prestogroup.com

Chennai

A-3, First Floor, Sri Sathya Sai Building 755, Poonamallee High Road, Kilpauk Chennai- 600 010. Tamil Nadu
 P : +91 044 43865260, 43838372
 E : south@prestogroup.com